PACKAGED SYSTEMS

MicroTherm CMX0

Circulating Oil Temperature Control System

- · Heat Transfer Fluids to 550°F
- · 6 24 kW (15 81Mbh)
- · 240 and 480V, 3 Phase, 60 Hz
- Non-Pressurized (Atmospheric) Operation
- 0.430" Dia. Steel Sheath Elements
- · 3 hp Centrifugal Pump
- Electronic Digital Temperature and Process Control
- NEMA 1 Electrical Enclosure
- Pressure Gauges Monitor
 Pressure To And From Process
- Compact, Portable Cabinet with Casters
- Integral Expansion Tank with Atmospheric Vent
- Optional Closed-Loop Cooling (3.2 Ft²)

Applications

Chromalox Compact Oil Temperature Controllers are engineered to operate up to 550°F at atmospheric pressure (non-pressurized). They are particularly useful in the plastics industry for use with plastic materials that require higher temperatures than can be achieved by hot water systems.

- Injection Molding Machines Thermosplastics and Thermosets
- · Platens and Dies
- · Rolls, Laminating and Calendering
- · Pipeline Heating and Tracing
- · Jacketed Vessels and Tanks

Features

This product is pre-piped with pump, heaters and expansion tank. 1.5" NPT piping connections for oil provide for convenient hook up to external high temperature hoses or piping. All wiring conforms to NEC requirements.



Specifications

Weight:	355lbs
(does not incude packag	ging)
Size:	45"H x 19"W x 38"D

Ordering information

CMX0-550											
	k۷	<i></i>									
	6,	9, 1	2, 1	18, 2	4*		*24k	W in	480V on	ly	
		Co	ooli	ng							
		H	1	Heat	Only	/					
		(;	Heat/	/Coo	l					
			1	Volta	ige						
			_	240	0 2	240	/ 3P	Н		400	400V 3PH
				480	0 4	۱80۱	/ 3P	Н		575	575V 3PH
					(Cont	tacto	r or	SCR		
						0	Def	inite	purpose (contacto	r
						2	SCF	}			
							Con	troll	er		
							0	408	1-UOSRF	R-23000	Controller
							2	408	2-RPSRF	R-44010	Controller
								Enc	losure di	sconnec	t
								0	None		
								1	Enclosu	re discor	nnect
									Piping		
									0	NPT	
									1	Flange	
CMX0-550	24	4 (;	480	0	2	0	0	0	Typica	l Model Number

Stocked Models:

kW	Volts	Cooling	Model	Part Number
12	480	Heat Only	CMXO-550 12H 480 0000	307419-032
12	480	Heat / Cool	CMXO-550 12C 480 2010	307419-033
24	480	Heat Only	CMXO-550 24H 480 0000	307419-034
24	480	Heat / Cool	CMXO-550 24C 480 2010	307419-035

